


| 管径称  | 適合配管径 (A) | t×B    | d    | 締付ボルトナット | C  | H   |
|------|-----------|--------|------|----------|----|-----|
| 15A  | 21.7      | 2.0×25 | W3/8 | M6×20    | 24 | 75  |
| 20A  | 27.2      | 2.0×25 | W3/8 | M6×20    | 24 | 78  |
| 25A  | 34.0      | 2.0×25 | W3/8 | M6×20    | 24 | 84  |
| 32A  | 42.7      | 2.0×25 | W3/8 | M6×25    | 24 | 87  |
| 40A  | 48.6      | 2.0×25 | W3/8 | M6×25    | 24 | 90  |
| 50A  | 60.5      | 2.0×25 | W3/8 | M6×25    | 24 | 93  |
| 65A  | 76.3      | 2.0×25 | W3/8 | M8×25    | 28 | 106 |
| 80A  | 89.1      | 2.0×25 | W3/8 | M8×25    | 28 | 111 |
| 90A  | 101.6     | 2.0×25 | W3/8 | M8×25    | 24 | 114 |
| 100A | 114.3     | 2.0×25 | W3/8 | M8×25    | 28 | 124 |
| 125A | 139.8     | 3.0×32 | W1/2 | M10×35   | 32 | 155 |
| 150A | 165.2     | 3.0×32 | W1/2 | M10×35   | 32 | 166 |

|  |    |                       |      |             |                |
|--|----|-----------------------|------|-------------|----------------|
| 承認   | 検図 | 名称<br>ステンレス蝶番式吊バンドタン付 |      |             | 尺度<br>1:1      |
|  |    | 材質<br>SUS304          | 表面処理 |             |                |
| 設計   | 製図 | 板厚                    | 単重   | 角法<br>第三角法  |                |
|  |    | 図番<br>10110010106     |      |             | RevNo.<br>△2-3 |
|  <b>日栄インテック株式会社</b> 管材事業部 |    |                       |      | SHEET<br>A3 |                |