



管径称	適合管外径 (A)	保温厚 (T)					t
		20 P	25 P	30 P	40 P	50 P	
8A	9.53	62	72	82	102	122	1.5
10A	12.7	65	75	85	105	125	1.5
15A	15.88	68	78	88	108	128	1.5
19A	19.05	72	82	92	112	131	1.5
20A	22.22	75	85	95	115	135	1.5
	25.4	78	88	98	118	138	1.5
25A	28.58	81	91	101	121	141	1.5
	31.8	84	94	104	124	144	1.5
32A	34.92	87	97	107	127	147	1.5
	38.1	91	101	111	131	151	1.5
40A	41.28	94	104	114	134	154	1.5
	50.8	103	113	123	143	163	1.5
50A	53.98	107	117	127	147	167	1.5
	63.5	117	127	137	157	177	2.0
65A	66.68	120	130	140	160	180	2.0
80A	79.38	133	143	153	173	193	2.0
100A	104.78	158	168	178	198	218	2.0

承認	検図	名称 ステンレスウレタンCM		
		材質 SUS304	表面処理	尺度 1:1.5
設計	製図	板厚	単重	角法 第三角法
		図番 10200040232		RevNo 1-2
 日栄インテック株式会社 管材事業部				SHEET A3